



Hot Water Bath for Hydrostatic Pressure Testing-120x50x70-2S

Description

- According to ISO 1167, ASDTM D 1598, ASTM D 1599 //
- Including 2 connection lines from the pressure unit //
- Temperature control from Room Temperature up to 95C //
- Pneumatic-operated door //
- Water circulation system for temperature homogeneity //
- Digital PID temperature controller //
- Elastomeric foam insulation for the lid //
- SS304 for contact surfaces with water //
- Outer body is powder-coated paint //
- Have a level control that ensures that the test medium is topped up automatically //
- The special circulation system guarantees high accuracy and uniform temperature distribution //
- The double insulation of the bath walls //
- Steam release out //
- Pneumatic-operated door //
- Quick-release couplings connections inside the bath (standard delivery is female G1/4") //
- High-quality stainless steel SS304 //
- Easy connection to pressure test units //
- Constant test temperatures thanks to highly-efficient water circulation and precise temperature control in the inner tank //
- High-quality stainless steel test tank //
- Double insulation of the basic tank and insulated lid for minimum energy loss //
- Option to connect a chiller and plate heat exchanger to provide efficient and environmentally-friendly water cooling for low test temperatures (on request of customer-standard delivery has not this heat exchanger) //
- Integrated monitoring of tank level and temperature //
- Number of suspension rails : 2 //
- All parts coming into contact with water is SS304 //
- Maximum temperature is 95C //
- Training video included //
- Flange type heater allows easy repair //

-
- Direct contact of temperature measurement sensor with water inside the tank //
 - Including two temperature sensor for controller and for the computer monitoring //
 - Easy access to internal parts for replacement //
 - Internal dimensions : 120x50x70 (WxDxH) cm

AHP PLASTIK MAKINA